



# Flange Resurfacing Services

Clamp Range from .9" to 10.3"


## Flange Facing Made Easy

The **FLANGE PRO** is a rugged, compact and ideal for quickly reconditioning rusty, scarred and worn flange gasket seats to like-new condition in minutes. This easy to operate flange facing tool is perfect for re-facing RF and FF flanges on site, in a fabrication/repair shop and it produces a perfectly precise phonographic finish.

The **FLANGE PRO** has a clamping range from .9" (22.86mm) to 10.3" (261.6mm) and can machine flanges with a reach up to 14" (355.6mm) O.D. Our proprietary clamping system is simple to configure and designed for fast set-up with accurate alignment. Cutting bits are double sided, long lasting, and specially formed to cut through a wide variety of material including carbon steel, stainless steel, alloyed steel, aluminum and cast iron.

Each tool kit comes ready to use in a sturdy carrying case that keeps everything conveniently organized and readily accessible.

Whether you are interested in buying or renting, the **FLANGE PRO** will provide you with the consistently accurate results and years of trouble free service.



### Key Features

Manually operated, no electrical, hydraulic, or air lines necessary

Smooth swing operation produces precise phonographic finish

I.D. Clamping Range of .9" to 10.3" with facing diameter up to 14"

Accurately mounts to the flange I.D. in seconds

Feeds available for smooth/stock finish in acc. with ASME B16.5

Cutting tool has neutral (straight) & 90 degree tool bit holders

Made of high-strength precision machined materials

Sturdy carry/transport case for managing all components


Available kits come ready to use

Strong hardware that is easy to use and makes setup fast


Saves time & money

For sale & rent

\*\* Hand Operated Flange Facer - 0.900" I.D. to 14" O.D.  
22.86mm I.D. to 355.6mm O.D.



Draw rod wrench and knurled knob give the tool a comfortable, ergonomic feel.



Alignment accuracy is easily achieved by our clamp rib and pad system.



Double sided insert provides long-lasting clean finished job after job.



Precision Filtration Products | Pennsburg, PA  
215-679-6645 | 215-679-6648  
sales@pfpusa.com | www.pfpusa.com







# Flange Resurfacing Services

Clamp Range from .9" to 10.3"

## Clamping Advantage

The **FLANGE PRO** uses one mandrel and two wedges to achieve the full clamping range of .9" (22.9mm) to 10.391" (263.9mm). This rugged proprietary clamping system is simple to set-up and attaches to the flange I.D. with consistent unmatched accuracy. All components are made of high strength precision machined materials for long service.



### Flange Machining Diameter Range


◦ .9" - 14" / 22.9mm - 355.6mm

### Inside Diameter Clamping Range

◦ .895" - 10.391" / 22.7mm - 263.9mm

### Weight Ready-To-Use

◦ 15.4 lbs. / 7Kg.



Precision Filtration Products | Pennsburg, PA  
215-679-6645 | 215-679-6648  
sales@pfpusa.com | www.pfpusa.com

